




Elegant LED safety luminaires with powder-coated cover designed for tool-less ceiling installation.

Technical data


- Material :** Aluminum / powder-coated steel-sheet
 - Illuminant :** LEDs
 - Nominal voltage DC :** 24V ± 20%
 - Nominal current :** 200 mA
 - Terminals :** 2.5 mm² for feed-through wiring
 - Temperature ta :** -15°C... +40°C
 - Protection category :** IP40
 - Protection class :** III
- acc. to EN 1838, EN 60598-2-22 and EN 55015

Housing-colours	Part.no.	Colour code
White (RAL 9016)	...	L04
White aluminium (RAL 9006)	...	L10
Stainless steel	...	L30
Special colours	...	L99

Attach the colour code to part number e.g. **800 014 LXX**

Ceiling mounting			
Mounting height [m]	[m]	[m]	[m]
2.5	3.7	8.5	
3.0	4.1	9.7	
4.0	4.7	11.5	
5.0	5.0	12.9	
6.0	5.1	13.9	
7.0	4.9	14.3	
8.0	4.5	14.4	
9.0	3.7	14.3	
10.0	2.5	13.8	


Minimum illumination 1.25 Lux (middle of escape route)
Measuring plane 2cm above floor level



SN 8124.1-41 LED round

Art.no. 810 121


Ceiling mounting



SN 8124.1-41 LED squared

Art.no. 810 123


Ceiling mounting



Supply unit

Art.no. 890 451 round
Art.no. 890 452 squared

Accessory



Mounting adapter

Art.no. 890 701

Optional accessory

