

Elegant LED safety luminaires with powder-coated cover designed and asymmetric light distribution.

Technical data


- Material :** Aluminum / powder-coated steel-sheet
 - Illuminant :** LEDs
 - Nominal voltage DC :** 24V ± 20%
 - Nominal current :** 80 mA
 - Terminals :** 2.5 mm² for feed-through wiring
 - Temperature ta :** -15°C... +40°C
 - Protection category :** IP40
 - Protection class :** III
- acc. to EN 1838, EN 60598-2-22 and EN 55015

Housing-colours	Part.no.	Colour code
White (RAL 9016)	...	L04
White aluminium (RAL 9006)	...	L10
Stainless steel	...	L30
Special colours	...	L99

Attach the colour code to part number e.g. **800 014 LXX**


Ceiling mounting				
Mounting height [m]	[m]	[m]	[m]	[m]
2.5	4.2	10.9	2.7	1.0
3.0	4.5	11.6	2.8	0.9
4.0	0.8	12.5	2.8	0.2

Minimum illumination 1.25 Lux (middle of escape route)
Measuring plane 2cm above floor level




SN 8127-11 LED round
Art.no.810 314

Ceiling mounting



SN 8127-11 LED squared
Art.no.810 315


Ceiling mounting



Supply unit

Art.no.890 451 round
Art.no.890 452 squared

Accessory



Mounting adapter

Art.no.890 701

Optional accessory

