

Discrete LED edge lights composed of high-quality anodised aluminium profile without any visible screws. Homogeneous illumination of the free hanging frameless 20 mm acrylic pictograph by state-of-the-art LED technology. Discreet housing thanks to latest 24V technology.

Technical data


- Viewing distance :** 22 m
Material : Aluminum
Illuminant : LEDs
Nominal voltage DC : 24V ± 20%
Nominal current : 125 mA
Terminals : 2.5 mm² for feed-through wiring
Temperature ta : -15°C... +40°C
Protection category : IP40
Protection class : III
 acc. to DIN EN 60598-1, DIN EN 60598-2-22, DIN 4844-1 and DIN EN 1838

Pictograms exchangeable without tools

SNP 1216 D LED 24V

Art.no. 810 002


Ceiling mounting



SNP 1216 PM LED 24V

Art.no. 810 003


Parallel to wall mounting



Mounting frame

Art.no. 890 405

Recessed ceiling mounting



Discrete LED edge lights composed of high-quality anodised aluminium profile without any visible screws. Homogeneous illumination of the free hanging frameless 20 mm acrylic pictograph by state-of-the-art LED technology. Discreet housing thanks to latest 24V technology.

Technical data

- Viewing distance :** 22 m
Material : Aluminum
Illuminant : LEDs
Nominal voltage DC : 24V ± 20%
Nominal current : 125 mA
Terminals : 2.5 mm² for feed-through wiring
Temperature ta : -15°C... +40°C
Protection category : IP40
Protection class : III


acc. to DIN EN 60598-1, DIN EN 60598-2-22, DIN 4844-1 and DIN EN 1838

Pictograms exchangeable without tools

SNP 1216 P LED 24V

Art.no. 810 004

Pendulum mounting

**SNP 1216 S LED 24V**

Art.no. 810 005

Cable suspension mounting

