

Double sided aluminium profile emergency exit luminaires with light output bottom side.
Homogeneous illumination by state-of-the-art LED technology with a luminance of >500cd/m².

Technical data

- Viewing distance :** 20 m
 - Material :** Aluminum
 - Illuminant :** LEDs
 - Nominal voltage AC :** 230V ± 10%, 50/60Hz
 - Nominal voltage DC :** 220V ± 20%
 - Nominal current :** 18 mA
 - Power consumption :** 6.1 VA
 - Terminals :** 2.5 mm² for feed-through wiring
 - Temperature ta :** -15°C... +40°C
 - Protection category :** IP40
 - Protection class :** I
- acc. to DIN EN 60598-1, DIN EN 60598-2-22, DIN 4844-1 and DIN EN 1838


Pictograms exchangeable without tools

Housing-colours	Part.no.	Colour code
Special colours	...	L99
Attach the colour code to part number e.g.	800 014	LXX

SNP 7286 D LED 230V

Ceiling mounting


Art.no. 807 576 - J/SV
Art.no. 807 571 - SKÜ
Art.no. 807 596 - NE/SV



SNP 7286 P LED 230V

Pendulum mounting


Art.no. 807 578 - J/SV
Art.no. 807 574 - SKÜ
Art.no. 807 598 - NE/SV



SNP 7286 WA LED 230V

Wall bracket mounting

Art.no. 807 579 - J/SV
Art.no. 807 575 - SKÜ
Art.no. 807 599 - NE/SV



SNP 7286 K LED 230V

Chain mounting

Art.no. 807 577 - J/SV
Art.no. 807 573 - SKÜ
Art.no. 807 597 - NE/SV

