

Single sided emergency exit luminaires made of robust, brushed stainless steel with high protection category. Homogeneous illumination by state-of-the-art LED technology with a luminance of  $>500\text{cd/m}^2$ . Suitable for use in food industry or food processing plants with high demands on product hygiene.

**Technical data**

<b>Viewing distance :</b>	30 m
<b>Material :</b>	Stainless steel brushed
<b>Illuminant :</b>	LEDs
<b>Nominal voltage AC :</b>	230V $\pm$ 10%, 50/60Hz
<b>Nominal voltage DC :</b>	220V $\pm$ 20%
<b>Nominal current :</b>	18 mA
<b>Power consumption :</b>	6.1 VA
<b>Terminals :</b>	2.5 mm <sup>2</sup> for feed-through wiring
<b>Temperature ta :</b>	-15°C... +40°C
<b>Protection category :</b>	IP65
<b>Protection class :</b>	I

acc. to DIN EN 60598-1, DIN EN 60598-2-22, DIN 4844-1 and  
DIN EN 1838

Housing-colours	Part.no.	Colour code
White (RAL 9016)	...	L04
Dark grey (RAL 7015)	...	L16
Special colours	...	L99

Attach the colour code to  
part number e.g.

**800 014 LXX**

**SNP 808 LED 230V**

Art.no. 808 817 - J/SV  
Art.no. 808 807 - SKÜ  
Art.no. 808 813 - NE/SV

Wall mounting

