

LED safety luminaires for recessed wall- or stair-mounting with powder-coated cover. For installation in cavity-wall-box (Kaiser 9062-94).

**Technical data**

- Material :** powder-coated steel-sheet
  - Illuminant :** LEDs
  - Nominal voltage AC :** 230V ± 10%, 50/60Hz
  - Nominal voltage DC :** 220V ± 20%
  - Nominal current :** 18 mA
  - Power consumption :** 6.1 VA
  - Terminals :** 2.5 mm<sup>2</sup> for feed-through wiring
  - Temperature ta :** -15°C... +40°C
  - Protection category :** IP20
  - Protection class :** I
- acc. to EN 1838, EN 60598-2-22 and EN 55015


Housing-colours	Part.no.	Colour code
White (RAL 9016)	...	L04
White aluminium (RAL 9006)	...	L10
Special colours	...	L99

Attach the colour code to part number e.g. **800 014 LXX**

**SN 6110 G LED 230V**

Art.no. 806 014 - J/SV  
Art.no. 806 013 - SKÜ  
Art.no. 806 015 - NE/SV



Recessed wall or stair mounting




**SN 6110 O LED 230V**

Art.no. 806 011 - J/SV  
Art.no. 806 010 - SKÜ  
Art.no. 806 012 - NE/SV

Recessed wall or stair mounting



**SN 6110 G LED**



**SN 6110 O LED**

